IN THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in this application:

What is claimed is:

1 to 6 (cancelled).

7(newly presented). A method of determining the time t_{HOB} to a desired Height Of Burst (HOB) of a projectile comprising the steps of:

    a. measuring the time t_a that it takes said projectile to reach its apogee after launch; and;

    b. calculating the time to the desired time of burse t_{HOB} based upon the t_a.

8(newly presented). The method of claim 7 wherein the calculating step b above comprises setting the t_{HOB} as a percentage X% of t_a wherein said percentage is less than 100% and wherein $t_{HOB} = t_a + X\%t_a$.

9(newly presented). The method of claim 8 wherein said percentage of t_a is calculated as follows:

If $t_a > 12$ seconds then down leg time = 90% of t_a

If 12 sec $> t_a > 9$ seconds then down leg time = 70% of t_a

If 9 sec $> t_a > 7$ seconds then down leg time = 10% of t_a

If $t_a < 7$ seconds then there may be a malfunction and the projectile should be disabled.

10(newly presented). The method of claim 7 wherein said step b is calculated as follows:

$$t_{HOB} = t_a + \sqrt{t_a^2 - 2 \times HOB/g} + C$$

    where g = 9.81 m/sec^2 = 32.2 ft/sec^2

    and C = correction factor.

11(newly presented). The method of claim 10 wherein said correction factor C is calculated as follows:

If t_a > 12 seconds then C = 1.0 sec

If 12 sec > t_a > 9 seconds then C = 0.75 sec

If 9 sec > t_a > 7 seconds then C = 0.5 sec

If t_a < 7 seconds then there may be a malfunction and the projectile should be disabled.

12(newly presented). The method of claim 1 wherein said determining Step A is performed by a fuse including a turbo alternator to determine t_a.